

## DAFTAR PUSTAKA

- [1] I. S. Mulyana, "Analisis Pengaruh Temperatur Pada Barell Terhadap Hasil Extrusi Dengan Material Daur Ulang Kulit Kabel Pvc," vol. 14, pp. 2013–2015, 2020.
- [2] Pristiansyah; Hardiansyah; Sugiyarto, "Manutech : Jurnal Teknologi Manufaktur Optimasi Parameter Proses 3D Printing FDM Terhadap Akurasi Dimensi Menggunakan Filament Eflex," *Manutech J. Teknol. Manufaktur*, vol. 11, no. 01, pp. 0–7, 2019, [Online]. Available: <https://media.neliti.com/media/publications/289929-optimasi-parameter-proses-3d-printing-fd-bc4a4103.pdf>
- [3] H. Tondi, "Rancang Bangun Mesin Ekstruder Filamen 3D Printer," *Skripsi Tek. Mesin, Fak. Teknol. Ind. Univ. Islam Indones.*, pp. 1–50, 2019.
- [4] G. Yuzan, "ANALISA PERPINDAHAN PANAS TABUNG BARREL PADA MESIN EXTRUDER PLASTIK," 2021.
- [5] P. Setyadi, N. G. Yoga, M. Rizqi, and F. N. Amsir, "The Simulation of Fluid Flow and Heat Transfer in a Fluidized Bed Spray Dryer with a Vortex Generator 30 ° toward the Y Axis," vol. 210, no. Best 2021, pp. 405–410, 2022.
- [6] Y. A. Cengel, *Heat transfer, second edition*. 1995.
- [7] M. Irsyad, "Karakteristik Koefisien Perpindahan Panas Konveksi," pp. 137–145, 2017.
- [8] R. B. LUBIS, "PERANCANGAN PROGRAM PRINTER 3D MENGGUNAKAN," 2020.
- [9] ohammad I. Fermi, "Pemanfaatan Metode Computational Fluid Dynamics (CFD) Dalam Perancangan Kompur Biomassa," *Teknobiologi*, vol. 1, no. February 2014, pp. 15–19, 2014.
- [10] B. Xia and D. W. Sun, "Applications of computational fluid dynamics (CFD) in the food industry: A review," *Comput. Electron. Agric.*, vol. 34, no. 1–3, pp. 5–24, 2002, doi: 10.1016/S0168-1699(01)00177-6.
- [11] R. A. Lestari and R. I. Lestari, "Analysis of Encapsulated Yeast in Computational Fluid Dynamics Approach," *Konversi*, vol. 8, no. 2, pp. 99–107, 2019, doi: 10.20527/k.v8i2.7203.

- [12] A. Fluent, *MAN - ANSYS Fluent User' s Guide Releasde 15.0*, vol. 15317, no. November. 2013.
- [13] Z. C. He *et al.*, “An edge-based smoothed tetrahedron finite element method (ES-T-FEM) for 3D static and dynamic problems,” *Comput. Mech.*, vol. 52, no. 1, pp. 221–236, 2013, doi: 10.1007/s00466-012-0809-4.

