

DAFTAR PUSTAKA

- Alabi, F. M., & Omojola, M. O. (2013). Potentials of Nigerian Calcined Kaolin as Paint Pigment. *African Journal of Pure and Applied Chemistry*, 7(12), 410–417.
- Allen, A., & Gergely, J. S. (1998). *Reaction of Titanium Chloride with Aluminum Compound, Oxygen and Boron Oxide*. <http://www.google.com/patents?id=3iAaAAAAEBAJ>
- Alobaidi, T. B., & Alwared, A. I. (2022). Biosynthetic of Titanium Dioxide Nanoparticles Using *Zizyphus spina-christi* Leaves Extract: Properties. *Journal of Ecological Engineering*, 23(1), 315–324.
- Anderson, A. M., Bruno, B. A., & Smith, L. S. (2013). Viscosity Measurement. In *Handbook of Measurement in Science and Engineering*. John Wiley & Sons, Inc.
- Asmaoğlu, S. (2011). *Synthesis and Characterization of Multi-Hollow Opaque Pigments*. Middle East Technical University.
- Assael, M. J., Kakosimos, K., Banish, R. M., Brillo, J., Egry, I., Brooks, R., Qusted, P. N., Mills, K. C., Nagashima, A., Sato, Y., & Wakeham, W. A. (2006). Reference data for the density and viscosity of liquid aluminum and liquid iron. *J. Phys. Chem. Ref. Data*, 35, 285–300.
- ASTM D2369-20 Standard Test Method For Volatile Content of Coatings*. (2020).
- ASTM D523-14 Standard Test Method for Specular Gloss*. (2018).
- Astria, F., Subito, M., & Nugraha, D. W. (2014). Rancang Bangun Alat Ukur pH dan Suhu Berbasis Short Message Service (SMS) Gateway. *Jurnal Mektrik*, 1(1), 47–55.
- Auger, J. C., Martinez, V. A., & Stout, B. (2009). Theoretical study of the scattering efficiency of rutile titanium dioxide pigments as a function of their spatial dispersion. *Journal of Coatings Technology and Research*, 6(1), 89–97.
- Bai, Y., Ding, H., & Zhang, X. (2015). The influence of hiding power of white pigment on film ratio. *J. Paint & Coatings Industry*, 45, 69–73.
- Bentley, J., & Turner, G. P. A. (1998). Introduction to Paint Chemistry and principles of paint technology. In *Introduction to Paint Chemistry and Principles of Paint Technology*. Chapman and Hall Publications. <https://doi.org/10.1007/978-1-4899-3180-1>
- Brainard, D. H. (2003). Color appearance and color difference specification. *Sci. Color*, 2, 191–216.
- Braun, J. H. (1997). Titanium dioxide – A review. *Journal of Coatings Technology*, 69(868), 59–72.
- Braun, J. H., Baidins, A., & Marganski, R. E. (1992). TiO₂ Pigment Technology: A Review. *Progress in Organic Coatings*, 20, 105–138.

- Brown, R. F. G., Carr, C., & Taylor, M. E. (1997). Effect of pigment volume concentration and latex particle size on pigment distribution. *Progress in Organic Coatings*, 30(3), 185–194.
- Calabrese, L., & Proverbio, E. (2019). A Brief Overview on the Anticorrosion Performances of Sol-Gel Zeolite Coatings. *Coatings*, 9.
- Cardinal, C. M., Francis, L. F., & Scriven, L. E. (2009). Drying and collapse of hollow latex. *J. Coat. Tech. Res.*, 6(4), 457–469.
- Carvalho, S. (2007). *Tintas Plásticas para Construção Civil*. Resiquímica.
- Commission Delegated Regulation (EU) 2020/217. (2019). https://eur-lex.europa.eu/eli/reg_del/2020/217/oj
- Connolly, E. M., Hughes, C. S., Myers, C. P., & Dean, J. C. (1986). *The US Paint Industry: Technology Trends, Markets, Raw Materials*. SRI International.
- Cuppo, F. L. S., García-Valenzuela, A., & Olivares, J. A. (2012). Influence of surface roughness on the diffuse to near-normal viewing reflectance factor of coatings and its consequences on color measurements. *Color Research & Application*, 38(3), 177–187.
- Debnath, N. C., & Kotkar, D. D. (1998). Theoretical studies of light scattering power. *Eur. Coat. J.*, 4/98, 264–269.
- Demyk, K., Jones, A. P., Dartois, E., Cox, P., & D’Hendecourt, L. (1999). The chemical composition of the silicate dust around RAFGL7009S and IRAS 19110+1045. *Astronomy and Astrophysics*, 349(1), 267–275.
- Diebold, M. P. (2004). Technical Challenges for the TiO₂ Industry. *JCT CoatingsTech.*, 1(1), 36–44.
- Diebold, M. P. (2019). Optimizing the benefits of TiO₂ in paints. *Journal of Coatings Technology and Research*, 17(1).
- Donath, E., Sukhorukov, G. B., Caruso, F., Davis, S. A., & Möhwald, H. (1998). Novel hollow polymer shells by colloid-templated assembly of polyelectrolytes. *Angewandte Chemie*, 37(16), 2201–2205.
- Eneh, O. C. (2016). A guide for the paint maker. In *Welfare & Industrial Promotions (WIPRO) International*. Welfare & Industrial Promotions (WIPRO) International.
- Feller, A., & Christian, H. D. (2002). The influence of selected synthetic aluminium silicates on physicochemical properties of emulsion paints. *Macromol. Symp.*, 187, 663–675.
- Fitzwater, S., & Hook, J. W. (1985). Dependent Scattering Theory; A New Approach to Predicting Scattering in Paints. *J. Coat. Tech. Res.*, 57(721), 39–47.
- Flick, E. W. (1989). *Handbook of Paint Raw Materials*, 2nd ed. Noyes Publications.

- Flory, P. J. (1995). *Principles of Polymer Chemistry*. Cornell University Press.
- Fu, S.-H., & Fang, K.-J. (2008). The Effect of pH Value on Properties of Waterborne Nanoscale Pigment and the Estimation of the Solvated Layer Thickness. *Journal of Dispersion Science and Technology*, 29(8), 1085–1091.
- Gázquez, M. J., Bolívar, J. P., García-Tenorio, R., & Galan, F. V. (2014). A Review of the Production Cycle of Titanium Dioxide Pigment. *Materials Sciences and Applications*, 5(7), 441–458.
- Ghosh, S., Warriar, K. G. K., & Damodaran, A. D. (1990). Thermally treated kaolin as an extender pigment. *J. Mater. Sci. Letts.*, 9(1), 1046–1048.
- Groeneveld, I., Kanelli, M., Ariese, F., & R. van Bommel, M. (2023). Parameters that affect the photodegradation of dyes and pigments in solution and on substrate – An overview. *Dyes and Pigments*, 210.
- Guo, G., Yu, J., Luo, Z., Zhou, L., Liang, H., Luo, F., & Qian, Z. (2011). Synthesis and characterization of poly(methyl methacrylate-butyl acrylate)/nano-titanium oxide composite particles. *J. Nanosci. Nanotechnol.*, 11(6), 4923–4928.
- Gysau, D. (2011). *Fillers for Paints*. Vincentz Network.
- Hassas, B. V., Karakaş, F., & Çelik, M. S. (2013). Substitution of TiO₂ with PCC (Precipitated Calcium Carbonate) In Waterborne Paints. *23rd International Mining Congress & Exhibition of Turkey (IMCET 2013)*.
- Hellström, K., Diószegi, A., & Diaconu, L. (2017). A Broad Literature Review of Density Measurements of Liquid Cast Iron. *Metals*, 7.
- Jnido, G., Ohms, G., & Viöl, W. (2019). Deposition of TiO₂ Thin Films on Wood Substrate by an Air Atmospheric Pressure Plasma Jet. *Coatings*, 9(7), 441.
- Joseph, R. (2003). Film thickness calculations. *Metal Finishing*, 101(12), 51–53.
- Karakaş, F., Hassas, B. V., & Çelik, M. S. (2015). Effect of precipitated calcium carbonate additions on waterborne paints at different pigment volume concentrations. *Progress in Organic Coatings*, 83, 64–70.
- Karakaya, E., Mavis, B., & Gündüz, G. (2016). Synthesis of opaque and colored hollow polymer pigments. *Polymer Engineering & Science*, 57(9), 913–920.
- Karkare, M. M. (2014). Choice of precursor not affecting the size of anatase TiO₂ nanoparticles but affecting morphology under broader view. *International Nano Letters*, 4(3), 111.
- Kent, J. A. (2012). Pigments, Paints, Polymer Coatings, Lacquers, and Printing Inks. In *Handbook of Industrial Chemistry and Biotechnology*. Springer Science Business Media.
- Khan, A. K., Ray, B. C., & Dolui, S. K. (2008). Preparation of core-shell emulsion polymer and optimization of shell composition with respect to

- opacity of paint film. *Progress in Organic Coatings*, 62(1), 65–70.
- Kirchner, J. (2014). Defoaming of coating systems. In *Additives for Waterborne Coatings* (pp. 39–55). Vincentz Network.
- Kleinsteinberg, F. (2019). Wetting- and dispersing additives. In *Additives for Waterborne Coatings*. <https://doi.org/10.1515/9783748602187-003>
- Kobayashi, H., Miyanaga, E., & Okubo, M. (2007). Preparation of multihollow polymer particles by seeded emulsion polymerization using seed particles with incorporated nonionic emulsifier. *Langmuir*, 23(17), 8703–8708.
- Koleske, J. V. (2012). Paint and Coating Testing Manual, 15th edition of the Gardner-Sward handbook. In *ASTM International*. ASTM International.
- Kostansek, E. (2007). Controlling particle dispersion in latex paints containing associative thickeners. *J. Coat. Technol. Res.*, 4(4), 375–388.
- Kumar, S. S. (2015). Applications of nano pigment particles for the development in corrosion and scratch resistance of epoxy-zeolite coatings. *International Journal of Engineering and Applied Sciences*, 2(11), 103–109.
- Learner, T. (1995). The use of a diamond cell for the FTIR characterisation of paints and varnishes available to twentieth century artists. *IRUG2 at V&A*.
- Lokhande, G. P., & Jagtap, R. N. (2016). Design and synthesis of polymeric dispersant for water-borne paint by atom transfer radical polymerization. *Designed Monomers and Polymers*, 19(3), 256–270.
- McDonald, C. J., & Devon, M. J. (2002). Hollow latex particles: synthesis and applications. *Adv. Colloid Interface Sci.*, 99(3), 181–213.
- Mokrzycki, W., & Tatol, M. (2011). Color difference Delta E - A survey. *Machine Graphics and Vision*, 20(4), 383–411.
- Mueller, B. (2010). *Understanding Additives*. Vincentz Network.
- Müller, B. (2019). Wetting and dispersing agents. In *Understanding Additives* (pp. 11–46). Vincentz Network.
- Narayan, R., & Raju, K. V. S. N. (2000). The use of calcined clay as part replacement of titanium dioxide in latex paint formulations. *Journal of Applied Polymer Science*, 77, 1029–1036.
- Nsib, M. F., Ayed, N., & Chevalier, Y. (2006). Selection of Dispersants for The Dispersion of Carbon Black in Organic Medium. *Progress in Organic Coating*, 55, 303–310.
- Nsib, M. F., Ayed, N., & Chevalier, Y. (2007). Selection of Dispersants for the Dispersion of C.I. Pigment Violet 23 In Organic Medium. *Dyes and Pigments*, 74, 133–140.
- Okubo, M., Ito, A., & Hashiba, A. (1996). Production of submicron-sized multihollow polymer particles having high transition temperatures by the stepwise alkali/acid method. *Colloid. Poly. Sci.*, 274(5), 428–432.

- Özdemir, M., Aytaç, A., & Deniz, V. (2017). Investigation into the surface properties of papers sized with styrene-acrylate-cationic monomer based terpolymers. *Acta Physica Polonica A*. <https://doi.org/10.12693/APhysPolA.131.178>
- Pintus, V., & Schreiner, M. (2010). Characterization and identification of acrylic binding media: influence of UV light on the ageing process. *Analytical and Bioanalytical Chemistry*, 399(9), 2961–2976.
- Popić, S., Ristić, I., Mičić, V., & Tanasić, J. (2021). The Effect Of Methyl Methacrylate On The Properties Of Synthesized Acrylate Emulsions. *Contemporary Materials*, 12(1). <https://doi.org/10.7251/comen2101071p>
- Qureshi, S. A. (2021). Effect of Operating Parameters and Particle Size of Calcium Carbonate on the Physical Properties of Latex Paint. *Biomed. J. Sci. & Tech. Res.*, 39(1).
- Ramli, R. A. (2017). Hollow polymer particles: a review. *RSC Advances*, 7(83), 52632–52650.
- Ruszala, M. J. A., Rowson, N. A., Grover, L. M., & Choudhery, R. A. (2015). Low Carbon Footprint TiO₂ Substitutes in Paint: A Review. *Journal of Chemical Engineering and Applications*, 6(5), 331–340.
- Sayes, C. M., Wahi, R., Kurian, P. A., Liu, Y., West, J. L., Ausman, K. D., Warheit, D. B., & Colvin, V. L. (2006). Correlating nanoscale titania structure with toxicity: a cytotoxicity and inflammatory response study with human dermal fibroblasts and human lung epithelial cells. *Toxicol. Sci.*, 92, 174–185.
- Schwartz, M., & Baumstark, R. (2001). *Waterbased acrylates for decorative coatings*. Vincentz.
- Shah, S., & Mahanwar, P. A. (2018). Review on Opacifying Polymeric Pigment: Reconceive Hiding. *Journal of Coating Science and Technology*, 5, 59–69.
- Sluiter, A., Hames, B., Hyman, D., Payne, C., Ruiz, R., Scarlata, C., Sluiter, J., Templeton, D., & Wolfe, J. (2008). *Determination of Total Solids in Biomass and Total Dissolved Solids in Liquid Process Samples*.
- SNI 3564:2009 Cat Tembok Emulsi. (2009).
- SNI 3564:2014 Cat Tembok Emulsi. (2014).
- Stieg, F. B. (1989). Effect of extender on crowding of titanium pigment. *J. Coat. Technol.*, 61(778).
- Subagja, R., Andriyah, L., & Lalasari, L. H. (2013). Titanium Dissolution from Indonesian Ilmenite. *International Journal Basic Applications Sciences IJBAS-IJENS*, 13(4), 97–103.
- Sulistyono, A., Wahyuni, S., & Kasmui. (2018). Sintesis dan Karakterisasi TiO₂ (Nanorod)-SiO₂ dan Aplikasinya dalam Cat Akrilik. *Indo. J. Chem. Sci.*, 7(1), 56–63.

- Talbert, R. (2008). *Paints Technology Handbook*. Taylor & Francis group.
- Thiele, E. S. (1998). *Scattering of Electromagnetic Radiation by Complex Microstructures in the Resonant Regime*. University of Pennsylvania.
- Wang, Y., Wu, T., Zhou, Y., Meng, C., Zhu, W., & Liu, L. (1971). TiO₂-based nanoheterostructures for promoting gas sensitivity performance: designs, developments, and prospects. *Sensors*, 17(9).
- Werner, R., Krysztafkiewicz, A., Dec, A., & Jesionowski, T. (2001). Effect of surface modification on physicochemical properties of precipitated sodium–aluminium silicate, used as a pigment in acrylic dispersion paints. *Dyes and Pigments*, 50(1), 41–54.
- Wicks, Z. W., J. (1993). Coatings. In *Kirk-Othmer encyclopedia of chemical technology*. 4th ed. John Wiley & Sons Inc.
- Yap, A. U., Sim, C. P., Loh, W. L., & Teo, J. H. (1999). Human-eye versus computerized color matching. *Oper Dent.*, 24(6), 358–363.
- Yarusova, S. B., Gordienko, P. S., Panasenko, A. E., Barinov, N. N., & Zemnukhova, L. A. (2019). Sorption Properties of Sodium and Potassium Aluminosilicates from Alkaline Hydrolyzates of Rice Straw. *Russian Journal of Physical Chemistry A*, 93(2), 333–337.
- Yazdimamaghani, M., Pourvala, T., Motamedi, E., Fathi, B., Vashae, D., & Tayebi, L. (2013). Synthesis and characterization of encapsulated nanosilica particles with an acrylic copolymer by in situ emulsion polymerization using thermoresponsive nonionic surfactant. *Materials*.
<https://doi.org/10.3390/ma6093727>
- Youssef, A. M. A. (2019). *Paints Industry: Raw materials & unit operations & Equipment & Manufacturing & Quality tests*. Higher Technological Institute-10Th of Ramadan City.